



DECLARATION OF PERFORMANCE

No: 0338-CPR-0046-2013

Terram 1B1

Fiberweb Maldon
Fiberweb Geosynthetics Ltd
Blackwater Trading Estate
The Causeway
Maldon CM9 4GG
United Kingdom

T: +44 (0)1621 874200
F: +44 (0)1621 874299
info@terram.com

Harmonised technical specification	Intended uses
EN 13252: 20010:/A1:2005 Geotextiles for drainage systems	f/f+S/d

Essential characteristics	Performance	
Tensile Strength	EN ISO 10319	MD 20.0kN/m (-2.0kN/m) CMD 15.5kN/m (-1.5kN/m)
Tensile Elongation	EN ISO 10319	MD 35% (±15%) CMD 35% (±15%)
Dynamic Perforation	EN ISO 13433	38mm (+5mm)
Resistance to static puncture	EN ISO 12236	3.3kN (-0.33kN)
Opening size	EN ISO 12956	75µm (± 20µm)
Water Permeability	EN ISO 11058	50.10 ⁻³ m/s (-15.10 ⁻³ m/s)
In-plane water flow capacity	EN ISO 12958 (soft platens)	65.10 ⁻⁵ m ² /s (-6.5.10 ⁻⁵ m ² /s)
Dangerous Substances	Less than required by national regulations within EU member states	

Note: Testing on Dynamic perforation/Opening Size and Water Permeability is performed on the Geotextile fabric prior to lamination and is based on a single geotextile .

Durability

To be covered within 2 weeks after installation

Predicted to be durable for more that 25 years for non-reinforcing applications in soils with a range pH 1 -14 and soil temperatures <25°C as referenced within Durability Assessment report 1

System: 2+

In case of the declaration of performance concerning a construction product covered by a harmonised standard: Notified factory production control certification body No. 0338 BTTG performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of the factory production control.

Authorised Representative: Andrew Leech—Innovation and Technical Director